





FINSEAL-11MP

Pouch pack machine for laundry soap (100g/500g/800g/1Kg packs, etc.)

FINSEAL-11MP

Pouch pack machine for laundry soap (100g/500g/800g/1Kg packs, etc.)

1 Day Finseal 11 MP Output = Productivity of 15 Men



Principal of operation

2 rows of soaps are placed edge ways on flat belt conveyor, either by link up conveyor (not a part of the of the machine) or manually. Autofeeder transfers these soaps to the infeed lug conveyor of the machine. Infeed conveyor then transfers multi soap into wrapping film that has been formed into a tube by means of forming folder. Bottom seal is made by three sets of rollers. Cross sealing and cutting knife separate the packed soaps. Heat sealable material like BOPP or laminates is used.

Standard features

- All surfaces over which soaps are transported are made of stainless steel
- Flat belt conveyor infeed with Transfer Unit
- Long seal is formed by means of three pairs of rollers, axes of which can be tilted to get best results
- · Torque slip clutch to prevent damage in case of accidental jams
- Low voltage heaters for safety
- Individual temperature controls for heaters
- Print registration unit for printed wrapper
- Heavy distortion-free cast structure

Optional features

- Date Printing unit
- Variable speed drive (AC frequency control)
- Castors for mobility of machine

Principal of operation

2 rows of soaps are placed edge ways on flat belt conveyor, either by link up conveyor (not a part of the of the machine) or manually. Autofeeder transfers these soaps to the infeed lug conveyor of the machine. Infeed conveyor then transfers multi soap into wrapping film that has been formed into a tube by means of forming folder. Bottom seal is made by three sets of rollers. Cross sealing and cutting knife separate the packed soaps. Heat sealable material like BOPP or laminates is used.

Specially designed for Laundry Bars & Detergent Bars or Cartonned Products. Multi-soap pack.













Key Highlights

- 1. Speed: upto 120 PPM (Single Pack). Upto 60 PPM (Multiple Pack)
- 2. Infeed to the machine by means of easy to load flat belt conveyor carrying two rows of products
- 3. Easy size change
- 4. Elegant packing with gussetting option.
- 5. High productivity
- Gentle handling of product

Product Size (in mm)

	L	W	Н
MIN.	60	40	25
MAX.	220	100	65

- All minimum and maximum sizes are not valid at same time
- Other dimensions can be considered on request.
- Power: 2.5 KW/440V, 3 Phase, 50/60 Hz









Khosla Precisions

93 Industrial Area, Ph-I, Panchkula 134108, Haryana, INDIA Tel: 91-172-2562664, 76703, Fax: 91-172-2584510

E-mail: info@khoslamachines.com

